

- **Editorial-Chief**

Kiyoshi Takakuwa

- **Editorial Advisors**

Chisato Kobayashi
Kanae Ishida
Makoto Egashira
Koji Yasui
Hiroaki Kawachi
Masayuki Masuda
Akio Toda
Kiyoji Kawai
Tetsuji Ishikawa
Taizo Kittaka
Keiji Hatanaka
Itsuo Seki
Kazufumi Tanegashima
Kazumasa Mitsunaga

- **Vol. 127 Feature Articles Editor**

Junichiro Yamashita

- **Editorial Inquiries**

Makoto Egashira
 Corporate Total Productivity Management
 & Environmental Programs
 Fax +81-3-3218-2465

- **Product Inquiries**

Hiroaki Seki (p2-4)
 Mobile Phone Devices Marketing Sect.
 Tel: +81-3-3218-2980
 Seki.Hiroaki@cj.MitsubishiElectric.co.jp
<http://www.mitsubishichips.com/Global/>

Kazuhiko Sato (p5-16)
 High Frequency Device Marketing Sect.
 Tel: +81-3-3218-3014
 Sato.Kazuhiko@aj.MitsubishiElectric.co.jp
<http://www.mitsubishichips.com/Global/>

Jun Morita (p17-22)
 Optical Communication Devices Marketing
 Sect.
 Tel: +81-3-3218-3332
 Morita.Jun@ea.MitsubishiElectric.co.jp
<http://www.mitsubishichips.com/Global/>

Mitsubishi Electric Advance is published on
 line quarterly (in March, June, September,
 and December) by Mitsubishi Electric
 Corporation.
 Copyright © 2009 by Mitsubishi Electric
 Corporation; all rights reserved.
 Printed in Japan.

CONTENTS

Technical Reports

Overview	1
by <i>Kazuo Hayashi</i>	
A 2.4-V Low-Reference-Voltage Operation HBT-MMIC Power Amplifier Module for CDMA Applications	2
by <i>Takao Moriwaki</i> and <i>Kazuya Yamamoto</i>	
HBT High Power Amplifier Modules for WiMAX CPE Applications	5
by <i>Hitoshi Kurusu</i> and <i>Toshio Okuda</i>	
Microwave Triple Tuned Wideband VCO	8
by <i>Masaomi Tsuru</i> and <i>Ryoji Hayashi</i>	
60 W Output Power C-Band High-Efficiency Broadband GaN-HEMT	11
by <i>Yoshitsugu Yamamoto</i> and <i>Koji Yamanaka</i>	
Breakdown Voltage Enhancement in AlGaIn Channel Transistors	14
by <i>Takuma Nanjo</i> and <i>Muneyoshi Suita</i>	
High Sensitivity 2.5/10 Gbps InAlAs Avalanche Photodiodes	17
by <i>Eitaro Ishimura</i> and <i>Eiji Yagyu</i>	
43-Gbps EAM-LD Module / PD Module	20
by <i>Norio Okada</i>	